

COMPRESSORS

RECIPROCATING COMPRESSORS FOR PROFESSIONAL AND INDUSTRIAL USE



1-15 HP

GENERAL CATALOGUE

COAXIAL COMPRESSORS

2-3HP

CONTRACTOR RANGE



The new structure features a useful control panel that protects the pressure switch and pressure reducer.

The electric motor features overload protection. Double shockproof handle, double suction feet at front to improve stability during operation. Large wheels facilitate transportation, and two front wheels improve stability.



PIONEER



BIG PIONEER



SHUTTLE265M

Code	Product	⚡		🔧		🏠		📏		🌀		📏		📏			
		Volt/Ph	kW	HP	Model	liters	m ³ /h	c.f.m.	bar	psi	c.p.m.	n° ol.	n° st.	LxDxH (cm)	kg	lit	
COAXIAL OIL LESS COMPRESSORS WITH SPECIAL FRAME FOR SPECIAL APPLICATIONS																	
2.4	FOAA404FNM473	SHUTTLE OL232	230/1	1.5	2	OL232	218	13	7.7	10	145	2850	1	1	51 x 27 x 40	21	46.3
9.5	FOPP404FNM399	PIONEER OL 232	230/1	1.5	2	OL232	218	13	7.7	10	145	2850	1	1	39.5 x 32 x 63	22	48.5
20	FOPB404FNM474	BIG PIONEER OL232	230/1	1.5	2	OL232	218	13	7.7	10	145	2850	1	1	47 x 49 x 72	28	61.7
COAXIAL LUBRICATED SINGLE-PHASE COMPRESSORS WITH SPECIAL FRAME FOR SPECIAL APPLICATIONS																	
2.4	FMAA404FNM355	SHUTTLE 265M	230/1	1.5	2	MK265	250	15	8.8	10	145	2850	1	1	51 x 27 x 40	21.5	47.4
9.5	FLPP404FNM039	PIONEER/I 2500M	230/1	1.5	2	SF2500	185	11.1	6.5	8	116	2850	1	1	39.5 x 32 x 63	18	39.7
9.5	FMPP404FNM052	PIONEER/I 265M	230/1	1.5	2	MK265	250	15	8.8	10	145	2850	1	1	39.5 x 32 x 63	22	48.5
20	FMPB4G4FNM036	BIG PIONEER/I 285M	230/1	1.8	2.5	MK285	260	15.6	9.2	10	145	2850	1	1	47 x 49 x 72	30	66.1
20	FMPB504FNM038	BIG PIONEER/I 312M	230/1	2.2	3	MK312	284	17	10	10	145	2850	1	1	47 x 49 x 72	33.5	73.9
20	FVDC504FNM426	BIG PIONEER/I 4020M	230/1	2.2	3	VKM4020	356	21.2	12.6	9	131	2850	2V	1	47 x 49 x 72	37	81.6

COAXIAL COMPRESSORS

1.5-2HP

OILLESS RANGE



ENERGY6/1950



ENERGY12/1950



They are commanded by electro-mechanical pressure switch, an accessory unit with manometer and a universal quick coupler. Electro-mechanical pressure switch, accessory unit with double manometer and universal quick coupler. The electric motor features overload protection.



YAGO1850



CIAO6/1850



CIAO25/1850

L	Code	Product	⚡		🔌		🌀		➡		📏		🔄		📦		📐		
			Volt/ph	kW	HP	Model	l/min	m ³ /h	c.f.m.	bar	psi	rpm	n° cil.	n° st.	LiDol (cm)	kg	Lbs		
SINGLE-PHASE COMPRESSORS - 8 BAR																			
6	C6BB304FNM478	ENERGY 6 - 1950 - 1.5M NEW	230/1	1.1	1.5	XT1950	180	10.8	6.4	8	116	3400	1	1	35 x 31 x 37	9.5	20.9		
12	8213344FNM485	ENERGY 12 - 1970 - 1.5M NEW	230/1	1.1	1.5	XT1970	200	12.1	7.1	8	116	2950	1	1	46 x 44 x 42	14	30.8		
-	FOAA304FNM479	YAGO 1850+KIT	230/1	1.1	1.5	OL1850	179	10.7	6.3	8	116	2850	1	1	31 x 20.5 x 32.5	9	19.8		
6	FOBB304FNM003	CIAO 6/1850	230/1	1.1	1.5	OL1850	179	10.7	6.3	8	116	2850	1	1	33 x 25.5 x 50	11.5	25.4		
24	FOCC304FNM005	CIAO 25/1850	230/1	1.1	1.5	OL1850	179	10.7	6.3	8	116	2850	1	1	58 x 27 x 60	19	41.9		
-	FOAA404FNM481	YAGO 2350	230/1	1.5	2	OL2350	218	13	7.7	10	145	2850	1	1	31 x 20.5 x 32.5	11	24.2		
6	FOBB404FNM482	CIAO 6/2350	230/1	1.5	2	OL2350	218	13	7.7	10	145	2850	1	1	33 x 25.5 x 50	13.5	29.7		
24	FOCC404FNM483	CIAO 24/2350	230/1	1.5	2	OL2350	218	13	7.7	10	145	2850	1	1	58 x 27 x 60	21	46.2		
50	FODC404FNM484	CIAO 50/2350	230/1	1.5	2	OL2350	218	13	7.7	10	145	2850	1	1	83 x 35 x 62	28	61.6		

COAXIAL COMPRESSORS

2-2.5HP

LUBRICATED - AMICO RANGE



Electro-mechanical pressure switch, pressure reducer with double manometer and universal quick coupler. Rubber wheels facilitate transportation. Shockproof handle and 1.8 metre power cable. The electric motor features overload protection.



AMICO24/2400



AMICO25/2500



AMICO50/2600



AMICO50/2500

ℓ	Code	Product															
			Volt/ph	kW	HP	Model	l/min	m ³ /h	c.lm.	bar	psi	rpm	n° cil.	n° st.	l x D x H (cm)	kg	Lbs
SINGLE-PHASE COMPRESSORS - 8 BAR																	
24	FCCC404FNM422	AMICO 24/2400 NEW	230/1	1.5	2	MK2400	170	10	6.0	8	116	2850	1	1	57 x 25.5 x 59	22.5	49.6
50	FCDC404FNM427	AMICO 50/2400 NEW	230/1	1.5	2	MK2400	170	10	6.0	8	116	2850	1	1	79 x 31 x 67	29.3	64.6
24	FLCC404FNM001	AMICO 25/SF2500 - 2M	230/1	1.5	2	SF2500	185	11.1	6.5	8	116	2850	1	1	58 x 27 x 60	24	52.8
50	FLDC404FNM019	AMICO/I 50/SF2500 - 2M	230/1	1.5	2	SF2500	185	11.1	6.5	8	116	2850	1	1	83 x 35 x 62	31	57.2
24	FCCC4G4FNM423	AMICO 24/2600 NEW	230/1	1.8	2.5	MK2600	260	15.7	9.2	8	116	2850	1	1	58 x 27 x 60	26	57.3
50	FCDC4G4FNM428	AMICO 50/2600 NEW	230/1	1.8	2.5	MK2600	260	15.7	9.2	8	116	2850	1	1	83 x 35 x 62	32	70.5

COAXIAL COMPRESSORS

2-3HP

LUBRICATED - TIGER & SUPERTIGER RANGE



TIGER285M



SUPERTIGER285M



SUPERTIGER312M



SUPERTIGER4020M



Large wheels, two front handles and 2 feet to facilitate transportation and improve stability during operation.

Electro-mechanical pressure switch, pressure reducer with manometer and universal quick coupler. The electric motor features overload protection.

Code	Product	⚡ Volt/ph	⚙️ KW	⚙️ HP	⚙️ Model	➡️			⚙️		⚙️ r.p.m.	⚙️ n° oil	⚙️ n° st.	⚙️ LxDxH (cm)	⚙️		
						l/min	m³/h	c.l.m.	bar	psi					kg	lbs	
SINGLE-PHASE COMPRESSORS - 10 BAR																	
24	FMCC404FNM030	TIGER/I 265M	230/1	1.5	2	MK265	250	15	8.8	10	145	2850	1	1	58 x 31 x 61.5	24	52.8
24	FMCC4G4FNM033	TIGER/I 285M	230/1	1.8	2.5	MK285	260	15.6	9.2	10	145	2850	1	1	58 x 31 x 61.5	26	57.2
50	FMDC4G4FNM352	SUPERTIGER/I 285M	230/1	1.8	2.5	MK285	260	15.6	9.2	10	145	2850	1	1	84 x 40 x 67	35.5	78.1
50	FMDC504FNM076	SUPERTIGER/I 312M	230/1	2.2	3	MK312	284	17	10	10	145	2850	1	1	87 x 35 x 70	36.5	80.3
50	FVCC504FNM358	SUPERTIGER/I 4020M	230/1	2.2	3	VKM402	400	24	14.1	10	145	2850	2-V	1	87 x 35 x 71	39	85.8

BELT-DRIVEN COMPRESSORS

1-3HP

ADVANCED RANGE



Lubricated belt-driven single-stage two-cylinders compressor. Wheeled tanks to simplify transportation. Electro-mechanical pressure switch, pressure reducer with double manometer and universal quick coupler. Rubber wheels facilitate transportation. Shockproof handle and 1.8 metre power cable. The electric motor features overload protection with manual reset.



MK5-24



MK102/N -50-2M



MK102-100-2M

ℓ	Code	Product															
			Volt/ph	kW	HP	Model	l/min	m ³ /h	cm	bar	psi	rpm	n° cil.	n° st.	LxDxH (cm)	kg	lbs
SINGLE-STAGE SINGLE-PHASE COMPRESSORS ON WHEELS																	
24	FMCC204FNM348	MK 5 - 24 - 1M	230/1	0.75	1	MK5	120	6.1	3.6	10	145	1530	1	1	65 x 27 x 63	40.5	89.1
50	FMDC204FNM350	MK 5 - 50 - 1M	230/1	0.75	1	MK5	120	6.1	3.6	10	145	1530	1	1	83 x 42 x 71	57.5	127
50	BMDC404FNM698	MK 102/N - 50 - 2M	230/1	1.5	2	MK102/N	215	12.9	7.6	10	145	1375	2	1	87 x 40 x 70	45	99.2
50	BMDC404FNM699	MK 102 - 50 - 2M	230/1	1.5	2	MK102	235	14.1	8.3	10	145	1040	2	1	87 x 40 x 70	48.5	106.7
50	BNDC504FNM696	MK 103 - 50 - 3M	230/1	2.2	3	MK103	365	21.9	12.9	10	145	1375	2	1	87 x 40 x 70	57.5	126.5
100	BMFC404FNM707	MK 102/N - 100 - 2M	230/1	1.5	2	MK102/N	215	12.9	7.6	10	145	1375	2	1	107 x 45 x 77	60	132.3
100	BMFC404FNM776	MK 102 - 100 - 2M	230/1	1.5	2	MK102	235	14.1	8.3	10	145	1040	2	1	107 x 45 x 77	61.5	135.6
100	BNFC504FNM705	MK 103 - 100 - 3M	230/1	2.2	3	MK103	365	21.9	12.9	10	145	1375	2	1	107x 47.5 x 78	67.5	148.8
150	BMHC404FNM717	MK 102 - 150 - 2M	230/1	2	2	MK102	235	14.1	8.3	10	145	1040	2	1	133 x 50 x 89	91.5	201.9
150	BNLC504FNM716	MK 103 - 150 - 3M	230/1	2.2	3	MK103	365	21.9	12.9	10	145	1375	2	1	133 x 50 x 89	97.5	214.9
200	BNLC404FNM777	MK 102 - 200 - 2M	230/1	2	2	MK102	235	14.1	8.3	10	145	1040	2	1	146 x 55 x 95	97.5	215.2
200	BNLC504FNM722	MK 103 - 200 - 3M	230/1	2.2	3	MK103	365	21.9	12.9	10	145	1375	2	1	146 x 55 x 95	103.5	228.2

BELT-DRIVEN COMPRESSORS 2-5.5HP

ADVANCED RANGE



MK103/200/3



MK113/270/5.5

ℓ	Code	Product															
			Volt/ph	kW	HP	Model	l/min	m ³ /h	c.f.m.	bar	psi	rpm	m ³ /d.	n° st.	LxDxH (cm)	kg	lbs
SINGLE-STAGE THREE-PHASE COMPRESSORS ON WHEELS																	
50	BMDC441FNM700	MK 102 - 50 - 2	400/3	1.5	2	MK102	235	14.1	8.3	10	145	1040	2	1	87 x 40 x 70	48.5	106.7
50	BNDC541FNM697	MK 103 - 50 - 3	400/3	2.2	3	MK103	365	21.9	12.9	10	145	1375	2	1	87 x 40 x 70	54.5	119.7
100	BMFC441FNM709	MK 102 - 100 - 2	400/3	1.5	2	MK102	235	14.1	8.3	10	145	1040	2	1	107 x 47.5 x 77	64.5	142.2
100	BNFC541FNM706	MK 103 - 100 - 3	400/3	2.2	3	MK103	365	21.9	12.9	10	145	1375	2	1	107 x 47.5 x 78	70	154.3
150	BNHC541FNM791	MK 103 - 150 - 3	400/3	2.2	3	MK103	365	21.9	12.9	10	145	1375	2	1	133 x 49 x 89	80	176.4
200	BNLC541FNM721	MK 103 - 200 - 3	400/3	2.2	3	MK103	365	21.9	12.9	10	145	1375	2	1	146 x 55 x 95	90	198.4
200	BPLC601FNM723	MK 113 - 200 - 4	400/3	3	4	MK113	500	30	17.7	10	145	1300	2	1	146 x 55 x 98	100.5	221.6
200	BPNC601FNM744	MK 113 - 200 - 5.5	400/3	4	5.5	MK113	556	33.4	19.6	10	145	1445	2	1	146 x 55 x 98	106.5	234.8
270	BPNC701FNM745	MK 113 - 270 - 5.5	400/3	4	5.5	MK113	556	33.4	19.6	10	145	1445	2	1	155 x 59 x 110	126.5	278.9

BELT-DRIVEN COMPRESSORS

2-3HP

INDUSTRIAL RANGE V-TYPE ON WHEELS



Single-stage compressor pump with two V-posed cylinders. Splash lubrication, forced ventilation, cast iron cylinders, cast iron valve plates and steel valves.

Final manifolds for cooling the air entering to the tank. Electro-mechanical pressure switch. The electric motor features overload thermal protection with manual reset.



SKM10/50/2M



SKM12S/100/3M

ℓ	Code	Product															
			Volt/ph	kW	HP	Model	l/min.	m ³ /h	c.f.m.	bar	psi	r.p.m.	n° cil.	n° st.	LxDxH (cm)	kg	lit.
SINGLE-STAGE SINGLE-PHASE COMPRESSORS																	
50	BSDC404FNM701	SKM 10 - 50 - 2M	230/1	1.5	2	SKM10	240	14.4	8.4	10	145	1480	2V	1	83 x 42 x 70	62	136.4
50	BSDC504FNM780	SKM 12S - 50 - 3M	230/1	2.2	3	SKM12S	345	20.7	12.2	10	145	1200	2V	1	83 x 42 x 70	68	149.6
100	BSFC404FNM710	SKM 10 - 100 - 2M	230/1	1.5	2	SKM10	240	14.4	8.4	10	145	1480	2V	1	107 x 45 x 77	78	171.6
100	BSFC504FNM781	SKM 12S - 100 - 3M	230/1	2.2	3	SKM12S	345	20.7	12.2	10	145	1200	2V	1	107 x 45 x 77	84	184.8
150	BSHC404FNM718	SKM 10 - 150 - 2M	230/1	1.5	2	SKM10	240	14.4	8.4	10	145	1480	2V	1	133 x 49 x 89	97	213.4
150	BSHC504FNM784	SKM 12S - 150 - 3M	230/1	2.2	3	SKM12S	345	20.7	12.2	10	145	1200	2V	1	133 x 49 x 89	103	226.6
200	BSLC504FNM786	SKM 12S - 200 - 3M	230/1	2.2	3	SKM12S	345	20.7	12.2	10	145	1200	2V	1	141 x 56 x 95	127	279.4

BELT-DRIVEN COMPRESSORS

3-5.5HP

INDUSTRIAL RANGE V-TYPE ON WHEELS



SKM12S/150/3T



SKM15/270/5.5

Code	Product	⚡		🏠		🔧			📏		🔄		📐		🚚		
		Volt/ph	kW	HP	Model	l/min	m ³ /h	cfm	bar	psi	rpm	m ² cl.	m ² st.	(x)DxD (cm)	kg	lbs	
SINGLE-STAGE THREE-PHASE COMPRESSORS																	
50	BSDC541FNM782	SKM 12S - 50 - 3	400/3	2.2	3	SKM12S	345	20.7	12.2	10	145	1200	2V	1	83 x 42 x 70	68	149.6
100	BSFC541FNM783	SKM 12S - 100 - 3	400/3	2.2	3	SKM12S	345	20.7	12.2	10	145	1200	2V	1	107 x 45 x 77	84	184.8
150	BSHC541FNM785	SKM 12S - 150 - 3	400/3	2.2	3	SKM12S	345	20.7	12.2	10	145	1200	2V	1	133 x 49 x 89	103	226.6
200	BSLC541FNM787	SKM 12S - 200 - 3	400/3	2.2	3	SKM12S	345	20.7	12.2	10	145	1200	2V	1	141 x 56 x 95	127	279.4
200	BSLC701FNM724	SKM 15 - 200 - 5.5	400/3	4	5.5	SKM15	580	35	20.5	9	130	1250	2V	1	150 x 55 x 100	153	336.6
270	BSNC701FNM746	SKM 15 - 270 - 5.5	400/3	4	5.5	SKM15	580	35	20.5	9	130	1250	2V	1	155 x 60 x 110	172	378.4

BELT-DRIVEN COMPRESSORS

4-15HP

INDUSTRIAL RANGE V-TYPE STATIONARY



Single-stage compressor pump with 2 V-posed cylinders, Splash lubrication, forced ventilation, cast iron cylinders, cast iron valve plates and steel valves.

Final manifolds for cooling the air entering to the tank. Electro-mechanical pressure switch. The electric motor features overload thermal protection with manual reset.



SKJ75-270-7.5

Code	Product	⚡		🏠		Model	🔄			📏		rpm	m³/dl	m³/st	LxDxH (cm)	📦	
		Volt/ph	kW	HP	l/min		m³/h	c.lm.	bar	psi	kg					Unit	
SINGLE-STAGE THREE-PHASE COMPRESSORS																	
270	BSNN601FNM757	SKM 15 - 270F - 4	400/3	3	4	SKM15	445	26.7	15.6	9	130	965	2V	1	155 x 60 x 110	165	363
270	BSNN701FNM758	SKM 15 - 270F - 5.5	400/3	4	5.5	SKM15	580	35	20.5	9	130	1250	2V	1	155 x 60 x 110	171	376.2
270	BXNN801FNN115	SKM 20 - 270F - 7.5	400/3	5.5	7.5	SKM20	1207	72.4	42.6	8	116	930	2V	1	155 x 60 x 110	216	475.2
500	BXTN801FNN146	SKM 20 - 500F - 7.5	400/3	5.5	7.5	SKM20	1207	72.4	42.6	8	116	930	2V	1	200 x 61 x 127	310	682
500	BXTN901FNN147	SKM 26 - 500F - 10	400/3	7.5	10	SKM26	1473	88.7	52.4	8	116	715	2V	1	155 x 60 x 110	350	770
500	BXTNA01FNN148	SKM 26 - 500F - 15 NEW	400/3	11	15	SKM26	1719	102.7	60.7	8	116	834	2V	1	200 x 61 x 127	366	805.2
SINGLE-STAGE THREE-PHASE COMPRESSORS WITH 3 CYLINDERS																	
270	BJNN901FNM752	SKJ 75 - 270F - 7.5	400/3	5.5	7.5	SKJ75	895	53.7	31.3	8	116	980	3W	1	158 x 53 x 113	270	594
270	BJNN801FNM754	SKJ 100 - 270F - 10	400/3	7.5	10	SKJ100	1240	74.4	43.4	8	116	870	3W	1	158 x 53 x 113	280	616
500	BJTN801FNM736	SKJ 75 - 500F - 7.5	400/3	5.5	7.5	SKJ75	895	53.7	31.3	8	116	980	3W	1	200 x 60 x 123	300	660
500	BJTN801FNM738	SKJ 100 - 500F - 10	400/3	7.5	10	SKJ100	1240	74.4	43.4	8	116	870	3W	1	200 x 60 x 123	310	682

BELT-DRIVEN COMPRESSORS 5.5-10HP

INDUSTRIAL RANGE V-TYPE STATIONARY



SKB26-270F-10



SKB20-500F-7.5

l	Code	Product															
			Volt/ph	kW	HP	Model	l/min.	m ³ /h	c.f.m.	bar	psi	r.p.m.	m ³ /d.	n° st.	LxDxH (cm)	kg	Lbs
DOUBLE-STAGE THREE-PHASE COMPRESSORS																	
270	BXNN701FNM756	SKB 20 - 270F - 5.5	400/3	4	5.5	SKB20	625	37.5	21.9	10	145	965	2V	2	160 x 51 x 110	216	475.2
270	BXNN801FNM751	SKB 20 - 270F - 7.5	400/3	5.5	7.5	SKB20	800	48	28.3	10	145	1237	2V	2	160 x 51 x 110	235	517
270	BXNN801FNM759	SKB 26 - 270F - 7.5	400/3	5.5	7.5	SKB26	870	52.2	30.5	10	145	845	2V	2	160 x 55 x 121	272	598.4
270	BXNN901FNM760	SKB 26 - 270F - 10	400/3	7.5	10	SKB26	1290	77	45.4	10	145	1080	2V	2	160 x 55 x 121	278	611.6
500	BXTN801FNM735	SKB 20 - 500F - 7.5	400/3	5.5	7.5	SKB20	625	37.5	21.9	10	145	965	2V	2	200 x 61 x 120	310	682
500	BXTN801FNM741	SKB 26 - 500F - 7.5	400/3	5.5	7.5	SKB26	870	52.2	30.5	10	145	845	2V	2	200 x 61 x 127	354	778.8
500	BXTN901FNM742	SKB 26 - 500F - 10	400/3	7.5	10	SKB26	1290	77	45.4	10	145	1080	2V	2	200 x 61 x 127	360	792

BELT-DRIVEN COMPRESSORS 1.5-7.5HP

VERTICAL TANK



CIAO50V/1850



MK103-90V-3M



SKM15-200V-5.5

ℓ	Code	Product			Model												
			Volt/ph	kW		HP	l/min.	m ³ /h	c.f.m.	bar	psi	c.p.m.	n° cil.	n° st.	LxDxH (cm)	kg	Lbs
OILLESS COMPRESSORS WITH VERTICAL TANK																	
50V	FODV304FNM480	CIAO 50V/1850	230/1	1.1	1.5	OL1850	179	10.7	6.3	8	116	2850	1	1	45 x 45 x 79	36.5	80.3
LUBRICATED COMPRESSORS WITH VERTICAL TANK																	
50V	FLDV404FNM477	SF 2500 - 50V - 2M	230/1	1.5	2	SF2500	185	11.1	6.5	8	116	2850	1	1	45 x 45 x 79	40	88
90V	BNGY504FNM694	MK 103 - 90V - 3M	230/1	2.2	3	MK103	365	21.9	12.9	10	145	1375	2	1	73 x 55 x 121	65	143
200V	BSLY701FNN149	SKM 15 - 200V - 5.5	400/3	4	5.5	SKM15	580	35	20.5	9	130	1250	2V	1			
270V	BXNY801FNN150	SKB 20 - 270V - 7.5	400/3	5.5	7.5	SKB20	800	48	28.3	10	145	1237	2V	2	72 x 72 x 177	280	616

GAS DRIVEN



SKM12S-100-5.5

GAS DRIVEN COMPRESSORS																	
100	BSFC7P1FNM790	SKM 12S - 100 - 5.5 CN PETROL ENGINE	gas	4	5.5	SKM12S	350	21	12.2	9	130	1320	2V	1	137 x 47 x 87	103	226.6



FINI ASIA PACIFIC

c/o CAMACO INTERNATIONAL LTD.
Unit 711, 7/F, Delta House
3 On Yiu Street, Shatin New Territories - Hong Kong
Tel. +852-23665562 - Fax +852-23665564
mail@camaco.com.hk - www.fini.com.cn



Company Quality
System Certification
ISO 9001:2008

FINI NUAIR S.p.A.

Registered Office: Via Einaudi 6 - 10070 Robassomero (TO) - Italy
Bologna Plant: Via Toscana 21 - 40069 Zola Predosa - Bologna - Italy
Tel. +39 051 6168111 - Fax +39 051 752408
Export Dept. Fax +39 051 7417272
www.finicompressors.com - info@finicompressors.it

FINI TAI SHAN Air Compressors Manufacturing Co. LTD.

Tai Shan City - Guang Dong Province - 529222 CHINA

Nu Air Shanghai Compressor and Tools Co. Ltd.

No. 15, 5842 Hu Nan Gong Road
Nanhui District - Shanghai - China
Tel. +86 2168220961 - Fax +86 2168220921